TCBM-38CL

Long Ø38 pull handle in AISI-316 stainless steel

REFERENCES	SERIES	FAMILY	REVISION
1605	TCBM-38CL	CBM · Pull handles	1 · Nov. 2026

MADE IN-HOUSE



DESCRIPTION

Long **Ø38 mm** pull handle for **glass doors** in **AISI-316 stainless steel**.

CBM pull handles are made exclusively of AISI-316 so that they keep their appearance over time, even when installed in aggressive environments such as the seafront.

AISI-316 steel
The highest-grade stainless steel, also for aggressive environments.

Ø38
38 mm diameter tube.

Single or double
For one side or both, with fixing nuts.

Long handle
L 2000 mm, centre distance 1800 mm.



Overview



Detail

AVAILABLE FINISHES



Polished



Matt



Black



Polished gold



Matt gold

REFERENCES AND VERSIONS

REFERENCE	SIZE (MM)	PRICE LIST CODES
1605	L 2000 · C.C. 1800	Double: **1605DB** · **1605DM** · **1605DN** Single: **1605SB** · **1605SM** · **1605SN**

Code suffix: D double · S single · B polished · M matt · N matt black RAL 9005 · A with adhesive. Finishes without a code: please ask.

Comercial CBM 95, S.L. · Talleres Blamar, S.A.
Can Bernat 4 · Pol. Ind. Torrent d'en Puig · 08358 Arenys de Munt (Barcelona, Spain)
T. +34 93 795 13 01 · info@blamar.com
cbmblamar.com

TCBM-38CL · Technical data

DIMENSIONS

2000 Total L	**1800** C.C.	**Ø38** profile

Dimensions in mm, according to the CBM price list.

SPECIFICATIONS

Application	**Glass doors**
Material	**AISI-316 stainless steel**
Profile	**Ø38**
Hole in the glass	**Ø12 mm**
Configuration	**Single (one side) or double (both sides)**
Finishes	**Polished, matt, matt black RAL 9005, polished gold and matt gold**
Thickness	**Any. If not specified, for 10 mm glass**

INSTALLATION

1. State the door thickness on your order. If not specified, it is supplied for 10 mm glass.
2. Drill the Ø12 mm holes in the glass at the chosen centre distance.
3. Fix the handle with the fixing nuts supplied.

PACKAGE CONTENTS

- TCBM-38CL pull handle
- Fixing nuts

ISO 9001 2015

Comercial CBM 95, S.L. certifies that this product is manufactured in its facilities in Arenys de Munt (Barcelona) following the quality standards of its quality manual, in accordance with ISO 9001:2015, certified by TÜV Rheinland (no. 0.04.09198).

